

(12) UK Patent Application (19) GB (11) 2 385 692 (13) A

(43) Date of Printing by UK Office 27.08.2003

(21) Application No 0306754.3

(22) Date of Filing 20.08.2002

(30) Priority Data

(31) PS1072

(32) 13.03.2002

(33) AU

(86) International Application Data

PCT/AU2002/001114 En 20.08.2002

(87) International Publication Data

WO2002/000000 En 01.01.2001

(71) Applicant(s)

Besdi Pty Ltd

(Incorporated in Australia)

2 Glenlee Close, Mount Kuring-Gai,

New South Wales 2080, Australia

(72) Inventor(s)

Kevin William Dinn

(74) Agent and/or Address for Service

A A Thornton & Co

235 High Holborn, LONDON, WC1V 7LE,

United Kingdom

(51) INT CL⁷

G06F 1/16 // H04M 1/02

(52) UK CL (Edition V)

G4A AKS

B6F FCBK

H4J JK J36Q

(56) Documents Cited by ISA

GB 2363290 A

GB 2317531 A

EP 1022544 A1

WO 2002/013001 A2

WO 2001/005047 A1

US 5953541 A

US 5797098 A

"It's a Nokia... Game Boy Advance?", Jørgen Sundgot, InfoSyncworld, 11 October 2001,

<<http://www.infosyncworld.com/news/n/986.html>>

"New Nokia 5510 is entertainment phone", Ana

Leticia Sigvartsen, InfoSatellite.com, 11 October 2001,

<http://www.infosatellite.com/news/2001/10/a111001nokia_5510.htm>

"Nokia 5510 User's Guide", Copyright 2001-2002,

Selected pages. Available at:

<http://nds1.nokia.com/phones/files/guides/5510_usersguide_en.pdf>

(58) continued overleaf

(54) Abstract Title

Device interface and text input system

(57) The invention relates to a small computing device, such as a PDA or mobile phone, with an improved interface. A row of multifunction buttons are provided on either side of the display screen. The screen can therefore extend over more of the face of the device. The functions of the keys can be "soft" and indicated on the display screen or "hard" and indicated on or near the keys. The screen may be a touch screen and the device may be wearable. There is also a method of text message entry wherein a text sense element suggests one or more characters which are the start or continuation or end of a word being inputted. The system predicts the possible characters from a tree structure and can prioritise the options based on past options.




Fig. 25

(

(

(58) Field of Search by ISA

INT CL⁷ G06F, H04M

Other: **ONLINE:** WPL, EPODOC, PAJ, Internet




Fig. 1




Fig. 2




Fig. 3




Fig. 4

2/13




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9








Fig. 10

*Fig. 11**Fig. 12**Fig. 13**Fig. 14*





Fig. 15

*Fig. 16*

7/13




Fig. 17




Fig. 18




Fig. 19




Fig. 20a




Fig. 20b




Fig. 20c




Fig. 20d




Fig. 20e




Fig. 20f




Fig. 21a



Fig. 21b




Fig. 21c




Fig. 21d




Fig. 21e




Fig. 21f




Fig. 22

IN-MEMORY TREE STRUCTURE			SECTION OF DATA FILE	
l	a	...	labour ... lay	
		d e r s h i p	lead	11721
		i n g	leader	8669
	a	g u e	leaders	7234
		r n i n g	leadership	4686
		s t	leading	9619
		v e i n g	league	8103
		d	learn	6204
	e	e d s	learning	4257
		f t	least	4642
		a l	leave	18388
		i s l a t i o n	leaving	9240
		s	led	15451
		n g t h	lee	3587
		s s	leeds	4522
		t t e r s	left	39454
		v e l s	leg	5333
		w i s	legal	13103
	i	...	legislation	6965
	o	...	legs	6507
	t	...	length	7171
	u	...	less	35669
	y	...	let	23322
			letter	13589
			letters	7880
			level	25360
			levels	11894
			lewis	3730
			liability ... living	
			loan ... lower	
			lid	
			lucky ... lunch	
			lying	

Fig. 23




Fig. 24




Fig. 25




Fig. 26

IMPROVED DEVICE INTERFACE

Field of the Invention

5 The present invention relates to a small computing device with an improved interface, and, particularly, but not exclusively, to a mobile communications device, such as a mobile telephone.

10 Background of the Invention

 It is desirable for small computing devices, by which we mean usually portable devices, such as lap-top-type computers and smaller, including mobile telephones, personal digital assistants, cameras and other devices, to
15 be as small as possible for convenience.

 The problem with making such devices small enough to carry is that it allows only a limited size for the interface. For example, in mobile telephones, a small
20 screen and traditional numeric keypad are provided for the interface with the user. The numeric keypad input has been used for standard telephones for years, and was merely transferred for use in mobile phones with no significant adaptation. As mobile telephones become
25 smaller and smaller, the traditional numeric keypad input becomes more and more difficult to operate. This is particularly the case where, as is usual for most mobile telephones today, it is required to input alphabetic characters in order to, for example, store contacts in the
30 memory of the mobile telephone.

 Further, the display screens provided for mobile telephones are, by necessity, also small where the phone is small. They are not able to provide, therefore, a view of a great deal of information at any one time.

35 There is a need for an improved interface for small computing devices, such as mobile telephones and PDAs.

Summary of the Invention

In accordance with a first aspect, the present invention provides a small computing device, including a housing and a display screen extending along the face of the housing lengthwise, a first plurality of keys positioned adjacent one side of the screen and a second plurality of keys positioned adjacent the opposite side of the screen.

Preferably, the display screen extends for the majority of the length of the face.

Preferably, by "small computing device" is meant laptop-type computer size or smaller, and is preferably PDA-type size or smaller, including mobile telephone size.

Preferably, the first and second plurality of keys are positioned in rows running parallel to the length of the display screen. Each row is preferably only one key in width.

Preferably, the small computing device further comprises a control means arranged to control operation of the small computing device, the control means being arranged to control the small computing device to operate in a plurality of operating modes, wherein the keys operate as multi-function keys.

Preferably, the control means is arranged to control the device such that the particular function of a key in a particular operating mode is designated by indicia appearing on the display screen. Preferably the indicia appear adjacent the associated key.

Preferably, the first plurality of keys comprises two or more keys and the second plurality of keys comprises two or more keys.

Preferably, the first plurality of keys comprises between four and ten keys and the second plurality of keys comprises between four and ten keys.

Preferably, the first plurality of keys comprises six to eight keys and the second plurality of keys comprises

six to eight keys.

Preferably, in one the plurality of operating modes, the keys are associated with numerics and operation of the keys is arranged to input numerals to the small computing
5 device.

Preferably, there are at least five keys either side and each of the keys are associated in one operating mode with each of the ten digits of the decimal numeral system appearing as indicia on the display screen.

10 Preferably, in one operating mode, a scrolling function is provided which enables information on the display screen to be scrolled. Preferably, the scrolling function has a plurality of modes of scrolling. Preferably, each of the keys is associated with one or
15 more of the modes of scrolling.

Preferably, the device does not include any standard numeric or alpha-numeric keypad. It may include a limited number of additional keys, such as "yes" or "no" and/or "direction" keys, but the majority of the functions of the
20 device are preferably carried out by the first and second plurality of keys.

Preferably, in one operating mode, a plurality of the first and second plurality of keys are associated with a plurality of menu options. Selection of a menu option by
25 actuating an associated key in this mode, then switches the device to a further operating mode where a plurality of the first and second plurality of keys are associated with a menu item within the selected menu option. Preferably, the number of menu items is equal to or less
30 than the number of the first and second plurality of keys, enabling selection of a menu item by a simple two step operation of the interface, the first step selecting the menu option, the second step selecting the menu item within the menu. Note that operation is not limited to
35 two step operation, and there may be modes where more than two steps of operation are implemented.

The small computing device preferably includes text

sense means implementing a text sense function to facilitate input of text to the device. In a first text input operating mode, a user can select characters (eg. alpha- numerics) utilising the first and second plurality of keys. When one or more characters have been selected, the text sense means may propose a word or further characters to go with the characters already selected, and the user may select or deny the word or further characters.

10 The text sense means may also be arranged to provide a suggestion without a user having first selected characters of the word ie. text sense may be arranged to provide a suggestion for the start of the word.

15 Note that the text sense means may not always provide a suggestion which completes a word, and may provide a selection of one (preferably more than one) characters that may continue a word.

20 Preferably the small computing device is communications device and is preferably a mobile telephone. Preferably, a speaker area is positioned on the face of the housing above the screen, for transmission of sound to the user.

25 The small computing device of the present invention preferably has the advantage that it uses multi-function keys positioned adjacent the display screen, rather than a conventional numeric keypad (such as used on conventional mobile telephones), which enables more room on a face of the device for the screen so that more information can be displayed. Further, because the interface preferably uses "soft" buttons (ie. the buttons are multi-function) the function of the device can be altered easily by altering the software/hardware that drives the device. The interface is totally flexible and not limited by any dedicated operation (as normally is the case with conventional alpha-numeric keypads).

35 The small computing device may be controlled by the control means in a hard key operating mode. In the hard

key operating mode, the keys are arranged to input data associated with hard labels appearing on the small computing device and not on the display screen (ie. not "soft" labels). For example, a plurality of the keys may be labelled with numerics and in a hard key operating mode may be operable to input numerics.

Preferably, a small computing device is arranged in one operating mode to act as a dedicated function device. Preferably, functions associated with the multi-function keys are pre-configurable and are arranged to operate in a dedicated mode ie. the multi-function keys become dedicated function keys. This feature can be used to implement small devices including telephones having dedicated operation. One example is a telephone which may be dedicated for operation by a particular person, such as a child, and be limited to, for example, being able to call only selected telephone numbers.

Functionality of the small device of the present invention may be implemented by appropriate software and/or hardware.

In accordance with a second aspect, the present invention provides a communications device including a housing and a display screen extending along a face of the housing lengthwise, a first plurality of keys positioned sequentially adjacent one side of the screen and a second plurality of keys positioned sequentially adjacent the opposite side of the screen, the device including means enabling the device to be worn by a user.

30 Brief Description of the Drawings

Features and advantages of the present invention will become apparent from the following description of embodiments thereof, by way of example only, with reference to the accompanying drawings, in which;

Figure 1 is a front view of a small computing device in accordance with an embodiment of the present invention,

in this example being a mobile telephone;

Figure 2 is a front view of a further embodiment of a small computing device in accordance with the present invention;

5 Figures 3 to 13 are schematic representations of an interface of a small device in accordance with an embodiment of the present invention, for the purpose of illustrating various functions of the interface;

10 Figure 14 is a front view of a further embodiment of a small computing device in accordance with the present invention, in the form of a mobile telephone;

15 Figure 15 shows further schematic representations of an interface for a small computing device in accordance with an embodiment of the present invention, illustrating further functionality of the interface;

Figure 16 is a schematic block diagram of componentry of an embodiment of the present invention in the form of a mobile telephone;

20 Figure 17 is a further diagram of an interface of a small device in accordance with an embodiment of the invention, illustrating a further functional operation;

25 Figure 18 is a front view of the further embodiment of a mobile telephone in accordance with the present invention, illustrating hard key labels for operation in a hard key mode;

Figure 19 is a front view of a further embodiment of a small computing device in accordance with the present invention, illustrating an icon interface operating mode;

30 Figures 20 and 21 illustrates views of two further embodiments of a small computing device in accordance with the present invention;

Figure 22 is a front view of a device in accordance with an embodiment of the present invention showing a further operating mode;

35 Figure 23 shows an extract from a memory tree structure for implementing text sense.

Figures 24 to 26 are front views of a device in

accordance with embodiments of the present invention showing further operating modes.

Description of Preferred Embodiment

5

The following description of an embodiment of the present invention relates to a mobile communications device, in particular a mobile telephone. The invention is not, however, limited to a communications device, and
10 may be implemented as any small computing device, such as a personal digital assistant (PDA).

A conventional mobile telephone comprises a controller for controlling operation of the telephone, usually in the form of a processor, a radio transceiver
15 for communicating voice and/or text messages to and from the telephone, and an interface for input and output by the user.

A typical mobile telephone includes a housing which mounts the processor, radio transceiver communications and
20 other required circuitry, the housing having one face which mounts the interface, comprising (usually) a twelve button numeric keypad, "yes" and "no" keys and "direction" keys, a display screen and a space above the display screen for a speaker area.

25 This traditional interface results in a number of disadvantages, particularly where there is a requirement for small telephone size. Firstly, the keypad area is very small, and operation is awkward.

Secondly, the display area is also very small so it
30 is not possible to display a great deal of information at any one of time.

The limitations of this interface are an even greater problem now that far more functionality is required of mobile telephones. Common activities on mobile telephones
35 include:

- Menu selections for controlling settings
- Managing and selecting from an address book

- Sending, receiving and viewing text messages
- Browsing Internet data in either WAP or HTML format
- Specialised applications such as calculators, games, world time clocks etc.

5 The traditional numeric keypad interface hampers these activities greatly as it is a far from ideal method of controlling text input. For example, in order to input text, it is necessary to actuate a key four times in some cases to enter a letter.

10 Figure 1 of the drawings is a front view of a mobile telephone in accordance with an embodiment of the present invention. The telephone includes a housing 1, which in this embodiment mounts internally mobile telephone circuitry (see later), and has a front face 2. The front
15 face 2 mounts an interface which includes a display screen 3. The display screen 3 may be any convenient type of display eg. LCD. The display screen 3, as can be seen, takes up the majority of length of the face 2 of the housing 1. This is a much larger display space than
20 typically available for a mobile telephone.

 Additionally, the interface includes a first row of keys 4 and a second row of keys 5, the rows 4 and 5 in this embodiment extending in a line along the face of the housing on either side of the display screen 3. Each of
25 the keys 6 in the rows 4 and 5 are controlled as "multi function" keys in this embodiment. The interface is arranged such that a function of a particular key 6 at any time will be indicated by dynamic labels appearing next to the key 6 on the display screen 3, controlled by the
30 device processor (see later). The functions change depending on the activity the user is performing.

 The interface does not include any standard alpha-numeric key pad. In this embodiment a "yes" 7 and "no" 8 key is included positioned below the screen, and can be
35 associated with the usual "yes" and "no" functions eg. to initiate a telephone call ("yes" button) or finish a telephone call ("no" button).

Space is provided for a speaker area 9 on the front face 2 above the screen 3.

With this format it is possible to perform all current cell phone activities using the multi-function keys and new functions such as electronic mail are made feasible. The format is sufficiently versatile to be more capable of implementing future functions, depending on software/hardware provided in the device. It is also possible that various "personal digital assistant" (PDA) - type functionality could also be implemented using this interface eg. calenders, diaries.

A further embodiment of a small device in accordance with the present invention is schematically illustrated in figure 2. Figure 2 illustrates a small device 10 which may resemble such items as a watch, pager or pendant. The device 10 includes a housing 11 which mounts on one face 12 an interface including a display screen 13 and first 14 and second 15 rows of keys 16. In this embodiment the key 16 may be on the side of the device rather than on the face 12, and in the figure 2, the areas 17, 18, 19 and 20 are folded down ie. they are the sides, top and bottom, of the housing 11. "Yes" 21 and "no" 22 buttons are provided at the bottom 17 of the device 10.

This small device may be a communications device, a PDA, or any other small computing device. One advantage of this type of device is that it could be worn rather than carried which means the user may have the device with them at all times. Such a device could become ubiquitous.

In the embodiments of both figure 1 and figure 2, because the keys are placed in a row, they can be conveniently separated so that a finger does not overlap more than one key when a key is pressed. This results in easy control of a small device compared to, for example, the standard alpha-numeric keypads on small telephones, which are very clumsy to deal with.

Another advantage of the arrangement of both figure 1 and figure 2 is the larger screen, which provides the

ability to be able to see more text at a time, see more of the context of what is being read. It is also possible that images and more complicated documents may be viewed.

It is believed that the interface also enables
5 faster, easier text entry (see later on how text may be entered) so that it is easier to use text based services such as SMS and e-mail. Further, because of the large screen and the multi-function keys it is possible to implement a simpler, more intuitive menu operation (see
10 later). The interface enables many options to be presented at once rather than one at a time as is conventional with typical mobile telephones.

Further, this device does not require any particularly new manufacturing techniques over those
15 already used for a conventional mobile telephone and PDAs. The internal hardware of a mobile telephone, for example, may be similar (although, of course it may vary). It is merely the arrangement of the display and the keys that is altered.

20 A major advantage, as discussed above, is that as functions and labels for the keys may be software driven, the functionality of the device can be altered merely by altering software. It is therefore possible to produce devices that have different functionality, but the same
25 hardware ie. the same interface and internal components. For mobile telephone type devices, this is presently very difficult because of the dedicated alpha-numeric interface. One particular advantage of this is that this is by altering software the language of operation of the
30 device can be altered. Operation could include operation in Chinese characters, for example, utilising the same interface and the multi-function keys.

The following description describes different functions that may be implemented in the mobile telephone
35 or other mobile communications device utilising this interface. It will be appreciated that the device of the present invention is not limited to the functionality

described in the following, however, and many different functions may be implemented with this device with this interface.

Figures 3 through 13 of the drawings are schematic representations of the interface of a device in accordance with an embodiment of the present invention, for the purposes of illustrating some of the functions which may be implemented utilising this interface.

In the diagrams of figures 3 to 13, similar reference numerals have been used to the embodiment of figure 1, to indicate the rows 4 and 5 of keys 6, "yes" 7 and "no" 8 keys and the display screen 3.

When illustrating operation of the device in the diagrams of figures 2 through to 13, with an unshaded key 6a pressing of that key switches operation of the device onto the next step. The shaded boxes 25 on the display screen are active labels which designate the function of the adjacent key. If a box 26 adjacent to a key is unshaded it means that the associated keys are not active in that operating mode. The area 26 may be blank or used for displaying data 27. Note that the reference numerals 6a, 25, 26 and 27 have been used only in figure 3. For the purposes of clarity, these reference numerals have been omitted from the other figures 4 through 13, instead the operation of the interface being indicated by appropriate shading as discussed with reference to figure 3.

Figure 22 illustrates an embodiment where the soft labels on the screen do not take up the whole screen width and entry may be made on the screen between the labels. In this case numeric entry 100 is indicated.

Numerical Entry

Figure 4 illustrates an operating mode enabling simple numeric entry into the device. Each of the keys 6 is associated with a numeral or a * or a #. This is

equivalent to a standard numeric keypad on, for example, a standard mobile telephone. The difference here is that the keys 6 are dynamic and this "numeric keypad" is one operating mode only. Pressing "yes" 7 enables the
 5 telephone connection and pressing "no" 8 would be used to hang up, disconnect or abort the function. Note that an area for display of the number that is input in may be provided on display screen 3 (area not shown).

10 Text Entry

Many options may be implemented for the entry of text. Current methods used on typical mobile phones such as the multi-press system (wherein one key may be pressed
 15 to choose between several letters) or more advanced methods such as the T9 (www.tegic.com) could be implemented utilising the device of the present invention, by simply making in one operating mode the 12 keys 6 of this embodiment correspond to the standard alpha-numeric
 20 keypad keys for a mobile telephone. With the extra flexibility of the dynamic labelling of the keys, however, it is possible to implement more powerful and user friendly text input.

The applicant's co-pending patent application
 25 (PCT/AU01/01467) describes a method and system for text entry which can be utilised by the device of the present invention. The disclosure of the referenced patent application is hereby incorporated in this application.

It is also possible to have text input on a more
 30 advanced level where knowledge of language allows the device to significantly streamline the process of word entry. Text entry will be described in more detail later.

Menuing

35

Typical mobile telephones allow selection from an array of menu options by requiring the user to navigate

through a "tree", generally one option at time, using "direction" keys. This limits the user to a "tunnel vision" view of the interface and results in many key presses required to perform any one function. In the device of this embodiment of the present invention, however, utilising the multi-functions keys, many menu options can be presented to the user at any one time and if it is desired any of those options may go on to a further menu of more options (depending upon the number of multi-function keys available). For example, with the twelve key embodiment illustrated in the drawings, a menu structure with 144 options could be implemented and the maximum number of key presses required for a user to get to any single option would be two (although other operating modes may require more). Figures 5 through 7 illustrates some typical menus that may be utilised in the small device of this embodiment. Figure 5 and 6 show twelve menu options, each one associated with a key 6, eg in figure 5 options include "call number", "send msg", "send email", "programs", "addresses", "info", "call name", "view msg", "view email", "games", "internet", "settings". In figure 6 the options include "text", "ring", "clock", "alert", "key sound", "key lock", "list", "answer mode", "voice ans", "store", "ph num", "more. . .".

Note that figure 6 represents "settings" menu selectable via the interface of figure 5. The figure 6 display also enable a selection of "more" settings.

In figure 7 (the "programs" menu) there are only eight options and the other 4 key 6 are not required. These options include "calculator", "calendar", "remote ctrl", "music", "world time", "timer", "ebooks", "vend".

It will be appreciated that any menu option may be included depending upon the functionality of the device.

35 Option Selection

Within any menu it is possible in the present device

make an operating function correspond to an option selection (ie. selection of a particular menu item within a menu). In the present embodiment, on-line screen labels for the option are highlighted to indicate the current selection state. In figures 8 through 11 this is illustrated by underlining in the diagrams.

Binary Option

A binary option is either on or off and may be toggled in place by pressing its associated key.

Figure 8 illustrates a text setting menu with the "key beep" off.

Figure 9 illustrates a text setting menu with the "key beep" on. This is a binary option.

Multiple Selection Option

A multiple selection option enables a user to choose one or more items from a list of several items.

Figure 10 illustrates the ring melody menu for a telephone with the original setting "Rivers of Babylon".

Figure 11 illustrates the ring melody menu with the setting changed (multiple selection option).

Scrolling

Figures 12 and 13 illustrate how scrolling of the display screen 3 may be implemented utilising this interface. In the case where a long document is received in the device, such as a text message, e-mail or Internet page, scrolling such as illustrated in figure 12 may be implemented. Using universally recognised symbols associated with keys 6 on the right hand side of the display screen 3, this operating mode implements scrolling. Indicia 30 indicates that pressing the associated key 6 would move the display to the top of the document. Indicia 31 indicates that pressing the associated key 6 would move the document up a page. Indicia 32 indicates that pressing the associated key 6

moves the document up a line. Indicia 33, 34 and 35 have the equivalent functions in the opposite direction to 32, 31 and 30 respectively.

Figure 12 illustrates scrolling as applied to a document. Figure 13 illustrates scrolling as applied to a menu. This option may be used when there are more menu options to display than will fit on the display screen. In this case, the row of buttons 4 is associated with menu selection and the row of buttons 5 on the right hand side is associated with the scrolling function. Figure 13 illustrates a phone book function where six addresses (of David Bowie, Dean Martin, Jerry Lewis, Jack Nicholson, John West and Mick Jagger) are visible at any one time. To select one that is visible the user would press the relevant associated button in the row 4 and to see more they use the scroll control associated with keys in row 5.

Text Sense

A text sense function utilising a device in accordance with the present invention will now be described with reference to figure 15. Figure 15 shows 8 diagrams of the interface of the small device of the present invention, each diagram illustrating a different stage in input of text into the device. The same reference numerals are used for components equivalent to the components already described above. Note that in the operating mode of figure 15, the two top keys on each of the rows 4 and 5 of the keys 6 are associated with "direction" indicia 40, 41, 42, 43. A space 44 on the display screen is available to indicate the results of characters entered using this operating mode. The other keys are associated with dynamic functions illustrating text entry, as will become clear from the following description.

The applicant's previous patent application (PCT/AU01/01467) discloses a system which may be used to

enter any symbol (text, numerics, punctuation etc) in a very flexible and efficient manner. The system is essentially "two-step". Referring to diagram 1 of figure 15, the four lower keys 6 in each row 4 and 5 are
5 associated in this operating mode with functionality which corresponds to the text input functionality described in applicant's earlier patent application. The "soft key" indicators include four soft keys 45, 46, 47, 48 which together offer "groups" of characters which make up the
10 standard Arabic alphabet. Soft key 48 also includes other characters such as "?" "." etc as illustrated. Selection of one of these soft keys by actuation of the associated key 6, results in a selection of that "group" of characters.

15 For example, if the user wishes to input the character "l" they select soft key 46 by actuating the associated key 6. This results in selection of the group of characters illustrated on the soft key 46 and switches the device to a further operating mode as illustrated in
20 diagram 2 of figure 15. In this operating mode, each of the lower four keys 6 of the rows 4 and 5 are associated with a soft key representing one of the characters of the group of the soft key 46 in diagram 1. Soft keys 50, 51, 52, 53, 54, 55, 56, 57 are associated with respectively
25 the characters "i", "j", "k", "l", "m", "n", "o" and "p". The user actuates the key associated with the soft key 53 and this results in input in the character "l" to the device.

In the system described in the applicant's earlier
30 patent application, at the same time as the character "l" is input by actuation of soft key 53, or after, the device switches back to the operating mode illustrated in diagram 1 and the user can select a further group of characters designating the next character that they wish to enter
35 into the device 44. This simple "two-step" character entry operation has significant advantages over conventional character entry, such as that utilising

conventional alpha-numeric key pads.

In an embodiment of the present invention, however, a further improvement may be achieved by utilising a "text sense" operating mode.

5 As well as the numeric and alphabet soft keys 45, 46, 47, 48, there are also numeral 49 soft keys, a key 60 for "space", a key 61 for "delete" and a key 62 for "more" options.

10 As the user enters text they are presented with "best guesses" of the next one or more characters they are entering. The user has the choice of selecting one of the "best guesses" and having that section of the word filled in for them or explicitly entering the next character. Which ever option, as soon as the action is complete, the
15 system takes another "guess" and the cycle repeats until the end of the word.

As a user gets further into a word, the number of possibilities for the word decreases dramatically. At the start of a word, the "best guess" may not include an
20 option for progressing the intended word. If this is the case, the user must select the next character explicitly and allow the text sense functionality to guess based on this more explicit start string.

Also, at the start of the word the permutations for
25 the conclusion for the word may be so great that text sense does not proffer the entire end of the word, just the next one, two or more character blocks.

30 Whatever the case, the end result is that the user can enter medium to large words with significantly less key strokes or button presses than if they had typed all the characters of the word.

Referring again to figure 15, the following is an example entry sequence which utilises text sense (in this example, to enter the word "letter").

35 1. This is the opening screen of the standard text entry system of applicant's earlier application. The user wants to enter "l" so they select the character group

- containing "l": "ijklmnop".
2. Each of the characters from the group is now presented to the user and they select "l".
 3. The user has now entered "l" as the start of their word and Text Sense is now guessing the next two characters of the word based on its knowledge of the language. Thus we would look for "et". There is "ea" and "eg" because these are a more likely 2 character sequence than "et" at this stage so we have to reject the option presented by pressing "no".
 4. We are back to the explicit character entry mode. We want to enter the letter "e" so we select "abcdefgh".
 5. And then we select "e".
 6. We have now entered the string "le" and Text Sense is having another guess at the rest of the word. It has determined that it can only offer the next single letter but as some of those options only have one word under them it has offered the entire rest of that word. For instance the dictionary only has one word starting with "len" and that is "length". So rather than offering "n" then "g", etc it offers the entire rest of the word. The "|" character at the end of the string indicates that that option will terminate the word. Note: the system has several "lea. . ." and "leg. . ." words but it has not proffered "a" or "e" at this stage as it has already been determined at stage 3 that the word being entered is none of these. We now select "t" to continue our word.
 7. Now that "let" has been entered, the system has only matches for the words "let", "letter" or "letters". As these will all fit on the screen it presents all three. Selecting "|" would terminate the word as it currently stands and give us "let". We select "ter|" which will add "ter" to our entry and terminate the word.
 8. Thus we have entered the word "letter".

In the above description, the numbers in the left hand column are equivalent to the numbering of the diagrams in figure 15. Reference numerals have not be
 5 designated for each of the soft keys of diagrams 3 through 8, for the purposes of clarity. The reader will appreciate that the characters indicated in the diagrams designate the functionality of the associated soft key ie. selection of that soft key selects and enters the
 10 characters that illustrated on that soft key. A "|" on a soft key indicates the end of a word.

The following description is of one method of implementing text sense note that text sense will be implemented by appropriate software running on the control
 15 means, to provide a text sense means. The following description of text sense implementation refers to figure 23.

Data Structure

20 The internal data of the system is built up from a list presented to the system which contains all the words upon which to base guesses as well as an integer indicating a frequency of usage of the word. The frequency number does not have an absolute significance,
 25 it is only a representation of the frequency of usage of the word in relation to other words in the file.

As words are fed into the system a letter by letter tree structure is built. For example all words starting with "I" have a pointer from the top "I" node. Under "I"
 30 is a node for every letter that any word has following the letter "I". This goes on down the line until the end of the word is reached. For each node down the line a count of the frequency of all the words below it in the tree is maintained. This represents the frequency value for all
 35 words that start with the string down to that node.

Note: in a standard implementation you would also include in-word punctuation characters as well such as ""

and "--"

Figure 23 is a representation of the raw data (on the right) and the corresponding tree structure (on the left) built up internally for words starting with "Ie".

5

Section of String to Present

Given the first character(s) of a word, the system travels down the tree to the node that represents that start string. For instance, given the string "let" it would first go to the top "l" node then the "e" node under that then "t" node under that. This would bring us to the node that is shaded in the table above.

Note: if in travelling down the tree, the letters indicated a node that didn't exist this would mean that the user had entered the start of a word that isn't in the dictionary and thus we would leave them to complete the word with explicit character entry.

Having got to the node for "let" we see that there are three possible words underneath ("let", "letter" and "letters") so we present all three as they will fit on the screen.

A more involved example is if the user has only entered "le" this brings us to the large "e" node on the left of the above table. As we can see, there are many words under this. We would first look down one character and find that there are 10 possibilities ("a", "d", "e", "f", "g", "n", "s", "t", "v", "w"). As we have 8 positions on the screen (not much less than 10) we go down another level to the next two characters on from "le". This then gives us 19 possibilities (ad, ag, ar, as, av, dl, el, ed, ft, gl, ga, gi, gs, ng, ss, tl, tt, ve, wi). This now significantly exceeds our 8 positions so out of the 19 possibilities we pick the 8 two character strings which have the highest frequency total for the tree below the, we then present the.

Strings not re-presented

As the word is entered it is often possible for a combination to be considered which has already been ruled out by a previous set. In our example entry sequence (above), in step 3 we were presented with "ea" and "eg" but we wanted "et" so we explicitly entered "e". Thus it would be possible at step 6 of the example to present "a" and "g" but this is unnecessary as we know that these are not part of the desired word. In order to avoid representing a word we flag all nodes that have been presented so that when we are selecting candidates we treat flagged nodes as if they were not there.

When the end of the word is reached the flags are reset ready for the next word.

Dynamic learning

As well as the initial word list that the system is loaded with, the system also optionally learn new words as the user uses them.

As words are entered that the system knows it boost the frequency value of word giving it greater priority in subsequent usages. When the user enters words that the system does not know then the system could add these to the word list so that they are available for guessing with in the next instance.

For this to work, the data set must be stored in persistent storage between activations of the system.

Figure 24 illustrates a front view of a device in accordance with an embodiment of the present invention illustrating one form of interface for text entry. Figure 25 illustrates another form of interface which is modelled on the T9 style text entry with predictive guesses shown by indicators 200, 201, 202.

Dedicated Keypad Operation

In accordance with a further embodiment of the present invention, the small device may be configured to
5 operate in a dedicated operating mode which is pre-configurable, either by the manufacturer or by a user of the device so that the device cannot be easily switched from this one operating mode (for example it may have to be returned to the manufacturer or alternatively a user
10 may have to enter a security code to switch the operating mode).

Utilising the present invention, because the keys can be associated with soft keys implementing any function which is enabled by the hardware/software of the device,
15 the device can be configured in any dedicated operating mode.

One example of an operating mode is described in the following, with reference to figure 17 of the drawings. Figure 17 is a further diagram illustrating use of the
20 interface of the small device of the present invention, in the case as applied to a mobile telephone. The same reference numerals have been used to designate the same components as in the previous drawings.

The small device of this embodiment of the present
25 invention has been pre-configured, either during manufacture or by application of a configuration step by a user (eg. a parent) to configure the telephone in a "kids" mode, as illustrated.

In this "dedicated" mode, the operation of the
30 telephone cannot be changed, unless it is reconfigured by the manufacturer or by the parent (on entry of an appropriate security code, or other security operation). In this "kids" mode the keys 6 in the left hand row are associated with soft keys which include limited operations
35 only such as "answer" 17, "hang up" 71 and stored numbers for dialling "mum" 72, "dad" 73, "school" 74 and "emergency" 75.

Such a pre-configured telephone could be provided for a child's use, in the sure knowledge that they could not use the phone to dial any other numbers, and also would find the telephone very simple to operate and use in an emergency or to call school, mum or dad (or any other pre-configured number that may be required).

Figure 26 illustrates a front view of a device in accordance with an embodiment of the invention in "kids" mode.

As discussed above, it will be appreciated that any functionality could be implemented in the pre-configured mode, and the invention is not limited a "kids" mode only.

The pre-configuration could take place at the factory ie. devices with this interface could be produced with dedicated functions, or a multi-function device may be produced in which at least a plurality of the keys may be "locked" into one particular function. Security means, such as a PIN, may be available to unlock function if it is wished to return the device to multi-function operation.

Hard Key Operating Mode

The control means may control the operation of the device to provide a "hard key" operating mode. In the hard key operating mode, operation of the keys is not associated with a soft label is on the display screen, instead a hard label is associated with the key, eg. on the key. Figure 18 illustrates a front view of a device in accordance with an embodiment of the present invention illustrating hard labels 110 on the key 6. In this embodiment, the hard labels are alpha-numerics. When switched to the hard key operating mode, all the display screen is available for information entry in accordance with the hard labels. The device may be switched between hard and "soft" operating modes.

There may be a number of hard operating modes.

Icon Operating Mode

Figure 9 illustrates an embodiment of a small device in accordance with the present invention which utilises icons to indicate functionality of the key 6 in an icon
 5 operating mode. The icons 111 may indicate any operating function which is implemented by the device eg. address book, diary, calendar, world time, etc.

Figures 20 and 21 illustrate a view of further
 10 embodiments of small computing devices in accordance with the present invention. Figure 20 shows a front view, figure 28, side view from one side (figure 20B) illustrating direction keys 112 on the side, side view from the other side (figure 20C) rear view (figure 20D)
 15 indicating a battery cover 113, top view (figure 20E) and bottom view (figure 20F). Figure 21 illustrates similar views for a further embodiment, with the same reference numerals indicating similar components.

It will be appreciated that functionality of the
 20 small device may be implemented by appropriate software and hardware which is well within the scope of the skilled person in order to implement the "soft key" and other functionality required. For the sake of completion, figure 16 is a block diagram which illustrates one way
 25 only in which the hardware of a mobile telephone in accordance with an embodiment of the present invention may be implemented. This hardware, generally designated by reference numeral 80 is mounted in the housing 1 of the small device.

30 The components include a control means in the form processing means 81, which may include an on-board or off-board memory and a processor(s) arranged to control operation of the device. The processing means 81 may in fact include multiple processes eg. SIM card, DSP (Digital
 35 Signal Processor) and conventional processor for controlling other operations of the device such as the interface operation. The control means may incorporate

any form of processor or arrangement of processors which can implement the functionality of the device described above.

The device also includes a microphone 83 and microphone input 82 into the processor 81. Voice output via the processor 81 is via an amplifier 82 and loud speaker 83. A radio transceiver 84 is provided for telecommunications reception and transmission via an antenna 85. A display driver 86 is arranged to drive the display 3 and a keypad sensor 87 is arranged to receive input from the rows 4 and 5 of keys 6. The functionality as described above will be implemented by the appropriate software.

Figure 14 illustrates further embodiment of a mobile telephone in accordance with the present invention. In addition to having the same components as the mobile telephone of figure 1 which are indicated by the same reference numerals, the telephone of the embodiment of figure 14 also includes "direction" key 100. The direction key may be used for such things as scrolling or controlling games.

The above described embodiment is a small device which has a communication function and is preferably a mobile telephone. The present invention is applicable to devices which do not necessarily have communications functions. For example, the present invention may be implemented as a PDA type device which does not include a communications function but which includes computing functions such as diary, calendar, etc.

Conveniently, the present invention may be implemented as a hybrid device which includes communication function which may also include functionality which is not normally seen in a conventional mobile telephone, such as functionality associated with a PDA, e-mail, calendar, calculator, address book, world time, alarm clock and others.

Modifications and variations as would be apparent to a skilled addressee are deemed to be within the scope of the present invention.

CLAIMS

1. A small computing device, including a housing and a display screen extending along a face of the housing lengthwise, a first plurality of keys positioned adjacent one side of the screen and a second plurality of keys positioned adjacent the opposite side of the screen.
2. A small computing device in accordance with claim 1, the first and second plurality of keys being positioned in rows extending substantially the same direction as the length of the face of the housing.
3. A small computing device in accordance with claim 2, each of the first and second plurality of keys being positioned in rows of single key width.
4. A small computing device in accordance with claim 1, 2 or 3, the first and second plurality of keys being positioned on the face of the housing.
5. A small computing device in accordance with claim 1, 2 or 3, the first and second plurality of keys being positioned on respective sides of the housing adjacent the face.
6. A small computing device in accordance with any one of the preceding claims, further comprising control means arranged to control operation of the small computing device, the control means being arranged to control the small computing device to operate of a plurality in operating modes wherein the keys operate as multi-function keys, the particular function of the key in a particular operating mode being designated by indicia appearing on the display screen.
7. A small computing device in accordance with claim 6, wherein the control means is arranged to control the small computing device so that the particular function of a key in a particular operating mode is designated by indicia appearing on the display screen adjacent the key.
8. A small computing device in accordance with any one of the preceding claims, wherein the first plurality of

keys comprises three or more keys and the second plurality of keys comprises three or more keys.

9. A small computing device in accordance with claim 8, wherein the first plurality of keys comprises between four
5 and ten keys inclusive and the second plurality of keys comprises between four and ten keys inclusive.

10. A small computing device in accordance with claim 9, wherein the first plurality of keys comprises between six and eight keys inclusive and the second plurality of keys
10 comprises between six and eight keys inclusive.

11. A small computing device in accordance with any one of the claims 6 to 10, wherein in one of the plurality of operating modes, at least a plurality of keys are associated with numerals, operation of the plurality of
15 keys resulting in the input of numerals.

12. A small computing device in accordance with claim 11, wherein the first plurality of keys comprises at least 5 keys and the second plurality of keys comprises at least 5 keys, and at least 5 keys of each of the first and
20 second plurality of keys are associated in one operating mode with each of the ten digits of the decimal numeral system appearing as indicia on the display screen.

13. A small computing device in accordance with any one of claims 6 to 12, wherein the control means is arranged
25 to control the small computing device in a hard key operating mode, and where at least a plurality of the keys are associated with hard labels which indicate function of the keys in the hard key operating mode.

14. A small computing device in accordance with claim 13,
30 wherein the hard labels are arranged on the keys.

15. A small computing device in accordance with claim 13 or claim 14, wherein the hard labels include numerics and in the hard key operating mode the control means controls the at least plurality of keys to input numerics
35 corresponding to the hard labels.

16. A small computing device in accordance with claim 13, 14 or 15, wherein the hard key operating mode the control

means is arranged to operate the at least plurality of the keys to input the characters from the Arabic alphabet, and the hard labels include Arabic characters.

17. A small computing device in accordance with any one of claims 6 to 16, wherein in one of the plurality of operating modes a plurality of the keys operate to provide a scrolling function, instructing the information on the display screen to be scrolled.

18. A small computing device in accordance with any one of claims 6 to 17, in a menu operating mode the control means being arranged to cause the display screen to display a plurality of menu options, each menu option being designated by an associated one of the plurality of keys, whereby one of the plurality of menu options may be selected by actuating the appropriate one of the plurality of keys.

19. A small computing device in accordance with claim 18, the control means being arranged, on actuation in the menu operating mode of one of the plurality of keys to select a menu option, to control the display to present a plurality of menu item for the particular menu option selected, each menu items being associated with one of the plurality of keys, whereby operation of a key results in selection of the associated menu item.

20. A small computing device in accordance with claim 19, the device being arranged so that the menu options include a number of menu items which are less than or equal to the number of the first and second plurality of keys, whereby selection of a menu item is a two key step process, comprising, firstly, selection of the menu option and, secondly, selection of the menu item within the menu option.

21. A small computing device in accordance with any one of claims 6 to 20 wherein in one of the plurality of operating modes the control means being arranged to control the display screen to present a plurality of items for selection, each of the items being associated with one

of the first or second plurality of keys, selection of the associated item being carried out on actuation of the associated key, the control means being arranged to enable that more than one of the displayed items can be selected.

5 22. A small computing device in accordance with any one of claims 6 to 20, wherein in one of the plurality of the operating modes the control means is arranged to control the display screen to present a plurality of items for selection, each one of the items being associated with one
10 of the first or second plurality of keys, selection of the associated item being carried out on selection of the associated key, the control means being arranged to enable only one of the displayed items to be selected.

23. A small computing device in accordance with any one
15 of claims 6 to 22, wherein in one operating mode, the control means is arranged to control the device so that selection of alpha- numerics may occur by operation of the keys, to enable entry of text to the device, and wherein the device is provided with text sense means arranged to
20 provide a suggestion of characters to be entered by a user of the device, and the control means controlling the display so that the text sense suggestion appears on the display screen associated with one of the plurality of the keys and may be selected by actuation of the associated
25 key.

24. A small computing device in accordance with claim 23, wherein the text sense means is arranged to provide a suggestion of characters which may include one or more characters but does not provide a complete word but only a
30 start or continuation of a word.

25. A small computing device in accordance with claim 23 or claim 24, wherein the text sense means is arranged to provide a suggestion of one or more of characters to complete the word.

35 26. A small computing device in accordance with any one of the preceding claims, and further comprising "yes" and "no" keys positioned below the screen.

27. A small computing device in accordance with any one of the preceding claims, and further comprising one or more "direction" keys positioned below the display screen.

28. A small computing device in accordance with any one
5 of the preceding claims, wherein the computing device includes means enabling it to be worn by a user.

29. A small computing device in accordance with any one of the preceding claims, the small computing device not being provided with a standard numeric keypad.

10 30. A small computing device in accordance with any one of the preceding claims, further comprising communication circuitry to enable a communications function.

31. A small computing device in accordance with claim 30, arranged as a mobile telephone.

15 32. A small computing device in accordance with any one of the preceding claims, wherein the device is pre-configured so that at least a plurality of the keys have dedicated, single function operation.

33. A small computing device in accordance with claim 31,
20 wherein at least a plurality of the keys have pre-configured dedicated single function operation, at least one of the functions instructing the communication circuitry to connect to a predetermined telephone number.

34. A small computing device in accordance with claim 31,
25 the device being configurable so that at least a plurality of the keys may be allocated a dedicated single function and locked so that they can only be operated to provide that single function.

35. A small computing device in accordance with claim 34,
30 wherein the single function effects an instruction to the communications circuitry to dial a predetermined telephone number.

36. A small computing device in accordance with any one of the preceding claims, further comprising a speaker area
35 positioned on the face of the display screen.

37. A small computing device in accordance with any one of the preceding claims, wherein the display screen is

arranged to be touch sensitive and the control means is arranged to control the device so that data may be input by touching the screen.

38. A small computing device in accordance with claim 20,
5 the mobile telephone not including a standard numeric key pad.

39. A small computing device in accordance with any one of the preceding claims, wherein the display screen extends for the majority of the length of the face.

10 40. A communications device including a housing and a display screen extending substantially the length of a face of the housing for the majority of the length of the face, a first plurality of keys positioned sequentially adjacent one side of the screen and a second plurality of
15 keys positioned sequentially adjacent the opposite side of the screen, the device including means enabling the device to be worn by a user.

41. A communications device in accordance with claim 40, wherein the device is substantially watch size and may be
20 worn as a watch or a pendant.

42. A communications device in accordance with claim 40 or 41, wherein the device is a mobile telephone.

43. A communications device in accordance with any one of claims 40, 41 or 42, the device further comprising
25 controls arranged to control operation of the communications device, a control means is being arranged to control the device to operate in the plurality of operating modes, wherein the keys operate as multi-function keys.

30 44. A communications device in accordance with claim 43, wherein a particular function of a key in a particular operating mode is designed by indicia appearing on the display screen.

45. A communications device in accordance with any one of
35 claims 40 to 44, wherein the first and second plurality of keys are positioned on the sides of the device adjacent the face.

46. A computer program arranged to control a small computing device to implement a small computing device of any one of claims 1 to 39.

5 47. A computer readable medium providing a computer program in accordance with claim 45.

48. A small computing device including a control means for controlling operation of the small computing device, a housing mounting the control means, a interface including a display screen and input means for inputting data, and a
10 text sense means arranged to provide a suggestion of characters, wherein the suggestion may include one or more characters but does not provide a complete word but only a start or continuation of a word.

49. A device in accordance with claim 48, wherein the
15 text sense means is arranged to provide a suggestion of one or more of the characters to complete the word.

50. A device in accordance with claim 48 or claim 49, wherein the text sense means is arranged to provide a suggestion of characters to commence a word.

20 51. A mobile telephone, including a housing and a display screen extending substantially along the length of the face of the housing for the majority of the length of the face, a first plurality of keys positioned adjacent one side of the screen a second plurality of keys positioned
25 adjacent the opposite side of the screen.

Amendments to the claims have been filed as followsCLAIMS

1. A mobile telephone, including a housing, a display screen extending along a face of the housing, a first
5 plurality of keys positioned adjacent one side of the screen and a second plurality of keys position adjacent the opposite side of the screen, a control means responsive to operation of the keys to implement at least a telephone number dialling function, the telephone not
10 including a conventional numeric-type keypad.
2. A mobile telephone in accordance with claim 1, the face of the housing having a major, longitudinal dimension and a minor, width dimension, the first and second plurality of keys being positioned in rows extending
15 substantially in the same direction as the longitudinal dimension of the face of the housing.
3. A mobile telephone in accordance with claim 2, each of the first and second plurality of keys being positioned in rows of single key width.
- 20 4. A mobile telephone in accordance with claim 1, 2 or 3, the first and second plurality of keys being positioned on the face of the housing.
5. A mobile telephone in accordance with claim 1, 2 or 3, the first and second plurality of keys being positioned
25 on respective sides of the housing adjacent the face.
6. A mobile telephone in accordance with any one of the preceding claims, the control means being arranged to control the mobile telephone to operate in a plurality of operating modes wherein the keys operate as multi-function
30 keys, the particular function of the key in a particular operating mode being designated by indicia appearing on the display screen.
7. A mobile telephone in accordance with claim 6, wherein the control means is arranged to control the
35 mobile telephone so that the particular function of a key in a particular operating mode is designated by indicia appearing on the display screen adjacent the key.

8. A mobile telephone in accordance with any one of the preceding claims, wherein the first plurality of keys comprises three or more keys and the second plurality of keys comprises three or more keys.
- 5 9. A mobile telephone in accordance with claim 6, wherein the first plurality of keys comprises between four and ten keys inclusive and the second plurality of keys comprises between four and ten keys inclusive.
- 10 10. A mobile telephone in accordance with claim 7, wherein the first plurality of keys comprises between six and eight keys inclusive and the second plurality of keys comprises between six and eight keys inclusive.
- 15 11. A mobile telephone in accordance with claims 9 to 10, wherein in one of the plurality of operating modes, at least a plurality of keys are associated with numerals, operation of the plurality of keys resulting in the input of numerals.
- 20 12. A mobile telephone in accordance with claim 11, wherein the first plurality of keys comprises at least 5 keys and the second plurality of keys comprises at least 5 keys, and at least 5 keys of each of the first and second plurality of keys are associated in one operating mode with each of the ten digits of the decimal numeral system appearing as indicia on the display screen.
- 25 13. A mobile telephone in accordance with any one of claims 9 to 12, wherein the control means is arranged to control the small computing device in a hard key operating mode, and where at least a plurality of the keys are associated with hard labels which indicate function of the
- 30 keys in the hard key operating mode.
14. A mobile telephone in accordance with claim 13, wherein the hard labels are arranged on the keys.
15. A mobile telephone in accordance with claim 13 or claim 14, wherein the hard labels include numerics and in
- 35 the hard key operating mode the control means controls the at least plurality of keys to input numerics corresponding to the hard labels.

16. A mobile telephone in accordance with claim 13, 14 or 15, wherein in the hard key operating mode the control means is arranged to operate the at least plurality of the keys to input the characters from the Arabic alphabet, and the hard labels include Arabic characters.
17. A mobile telephone in accordance with any one of claims 9 to 16, wherein in one of the plurality of operating modes a plurality of the keys operate to provide a scrolling function, instructing the information on the display screen to be scrolled.
18. A mobile telephone in accordance with any one of claims 9 to 17, wherein in a menu operating mode the control means being arranged to cause the display screen to display a plurality of menu options, each menu option being designated by an associated one of the plurality of keys, whereby one of the plurality of menu options may be selected by actuating the appropriate one of the plurality of keys.
19. A mobile telephone in accordance with claim 18, the control means being arranged, on actuation in the menu operating mode of one of the plurality of keys to select a menu option, to control the display to present a plurality of menu items for the particular menu option selected, each menu item being associated with one of the plurality of keys, whereby operation of a key results in selection of the associated menu item.
20. A mobile telephone in accordance with claim 19, the telephone being arranged so that the menu options include a number of menu items which are less than or equal to the number of the first and second plurality of keys, whereby selection of a menu item is a two key step process, comprising, firstly, selection of the menu option and, secondly, selection of the menu item within the menu option.
21. A mobile telephone in accordance with any one of claims 9 to 20 wherein in one of the plurality of operating modes the control means being arranged to

control the display screen to present a plurality of items for selection, each of the items being associated with one of the first or second plurality of keys, selection of the associated item being carried out on actuation of the
5 associated key, the control means being arranged to enable that more than one of the displayed items can be selected.

22. A mobile telephone in accordance with any one of claims 9 to 20, wherein in one of the plurality of the operating modes the control means is arranged to control
10 the display screen to present a plurality of items for selection, each one of the items being associated with one of the first or second plurality of keys, selection of the associated item being carried out on selection of the associated key, the control means being arranged to enable
15 only one of the displayed items to be selected.

23. A mobile telephone in accordance with any one of claims 9 to 22, wherein in one operating mode, the control means is arranged to control the telephone so that selection of alpha-numerics may occur by operation of the
20 keys, to enable entry of text to the telephone, and wherein the telephone is provided with text sense means arranged to provide a suggestion of characters to be entered by a user of the device, and the control means controlling the display so that the text sense suggestion
25 appears on the display screen associated with one of the plurality of the keys and may be selected by actuation of the associated key.

24. A mobile telephone in accordance with claim 23, wherein the text sense means is arranged to provide a
30 suggestion of characters which may include one or more characters but does not provide a complete word but only a start or continuation of a word.

25. A mobile telephone in accordance with claim 23 or claim 24, wherein the text sense means is arranged to
35 provide a suggestion of one or more of characters to complete the word.

26. A mobile telephone in accordance with any one of the

preceding claims, and further comprising "yes" and "no" keys positioned below the screen.

27. A mobile telephone in accordance with any one of the preceding claims, and further comprising one or more
5 "direction" keys positioned below the display screen.

28. A mobile telephone in accordance with any one of the preceding claims, wherein the device is pre-configured so that at least a plurality of the keys have dedicated, single function operation.

- 10 29. A mobile telephone in accordance with claim 28, wherein at least a plurality of the keys have pre-configured dedicated single function operation, at least one of the functions instructing the communication circuitry to connect to a predetermined telephone number.

- 15 30. A mobile telephone in accordance with claim 29, the device being configurable so that at least a plurality of the keys may be allocated a dedicated single function and locked so that they can only be operated to provide that single function.

- 20 31. A mobile telephone in accordance with claim 30, wherein the single function effects an instruction to the communications circuitry to dial a predetermined telephone number.

- 25 32. A mobile telephone in accordance with any one of the preceding claims, further comprising a speaker area positioned on the face above the display screen.

33. A mobile telephone in accordance with any one of the preceding claims, wherein the display screen is arranged to be touch sensitive and the control means is arranged to
30 control the device so that data may be input by touching the screen.



Application No: GB 0306754.3
Claims searched: 1 to 47 and 51

Examiner: Pierre Oliviere
Date of search: 4 June 2003

Patents Act 1977 : Search Report under Section 17

Documents considered to be relevant:

Category	Relevant to claims	Identity of document and passage or figure of particular relevance	
X	X: 1-4, 6-22, 26-47, 51 Y: 5, 23-25	WO 2002/013001 A2	(ARGO INTERACTIVE) The whole document.
X	X: 1-4, 6-22, 26-47, 51 Y: 5, 23-25	US 5953541 A	(KING) Figure 6B.
X	X: 1-4, 6-22, 26-47, 51 Y: 5, 23-25	WO 2001/005047 A1	(MOTOROLA) Figures 2 to 5.
X	X: 1-4, 6-22, 26-47, 51 Y: 5, 23-25	EP 1022644 A1	(XYBERNAUT) Figure 1.
X	1-22, 26-47, 51	GB 2363290 A	(ROSENBURG) Figure 2.
Y	23-25	US 5797098 A	(SCHROEDER) Figure 4.
Y	5	GB 2317531 A	(NEC) Figure 3B.

Categories:

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

Field of Search:

Search of GB, EP, WO & US patent documents classified in the following areas of the UKC^v:

B6F, G4A, H4J

Worldwide search of patent documents classified in the following areas of the IPC⁷:

G06F

The following online and other databases have been used in the preparation of this search report :

WPI, EPODOC, PAJ